



25w sterilizer pack - 1 spare lamp - double filter door - filters



Reference: packster25
EAN13: 3791054015214

25w sterilizer pack - 2 lamps - double-door filter water filtration - sediment filter and charcoal filter

Content of the UV 25W sterilizer pack:

- 1 double filter door - fastening square - 1 10 microns heat-welded sediment filter - 1 5 microns charcoal filter - 1 25W sterilizer with quartz bulb and transformer

- 1 Bulb 25W Philips

- 1 Philips 25 W replacement bulb

Key areas of application:

- Potabilisation of raw water from local resources (wells, boreholes, etc.), water stored in reserve and then recycled for sanitary use.

- Treatment of pool water.

- Destruction of organic pollutants.

- Destruction of algae spores, which prevents excessive proliferation of algae from your ponds, ponds, etc. ...



Technical features:

Outdoor dimensions: 63 x 600 mm

Stainless steel set

Weight: 1.65 Kg

Entry and exit diameter: 1/2 (15/21) "male threading"

Distance in/out of water: 55 mm

Maximum pressure: 6 bars

Recommended maximum speed: 1.8 m³ /h - 1,800 Litres per hour

Guarantee: 2 years

The Philips UV lamp is integrated into the body of the reactor and inside the quartz

Lamp power: 25 W Tube 4P SE TUV

Power voltage: 230 V mono

Average lifespan: 9,000 hours

Electric box:

Reactor-independent transformer 12V with Light indicator indicator of good functioning - Power: 230 V / 50 Hz - Power absorbed: 25 W

Important:

To optimize the efficiency of the UV sterilizer, it is important to ensure the good quality of the water to be treated. For this, it is strongly recommended to install one or more filters upstream, depending on the nature of the sediments to be filtered

What can make a difference



There are no known microorganisms resistant to Ultra Violet, unlike chlorine water treatment. UV is known to be highly effective against bacteria, viruses, algae. In practice, bacteria and viruses are the cause of many pathogenic diseases carried by water. Of these viruses, hepatitis virus and legionellosis have demonstrated the ability to survive for considerable periods of time in chlorine treatment, but are easily eliminated by UV treatment. For most microorganisms, the effectiveness of UV against microbiological contaminants such as bacteria and viruses generally exceeds 99.99%.

UV water treatment is very effective (up 99.99%) against: Salmonella (typhoid fever), salmonella enteritidis (gastroenteritis), vibrio cholerae (cholera), Tuberculosis of Mycobacterium (tuberculosis), Legionella pneumophila (Legionellosis), influenza virus, polio, and Hepatitis.

Double filter door with transparent jar to visualize the wear of consumables

Technical features:

- Dimensions: Width 340mm x Height 280mm x Depth 140mm
- Entry/Exit: 20/27 (3/4)
- Compatible with 9 - 3/4 inch cartridges - 10 thumbs
- Maximum pressure 4 bars

Supplied with tightening key and fastening square!

2-year warranty (except consumables)

Activated charcoal cartridge under film 9-3/4 inches - 10 inches

Activated charcoal filter cartridge for effective treatment of your water!

anti-taste and odours.

100% FOOD

Ultra-thin filtering of suspended particles in water larger than 5 microns - clay, rust, tartar particles, sand, etc.

Active coal for the treatment of heavy metals, pesticides, chlorine, herbicides and the bad tastes of your water.

9-3/4 Inches - 10 inches



Polypropylene replacement anti-sediment cartridge for filter door 10

CARTOUCHE THERMOSOUDEE (58 mm diameter) made of 100% polypropylene
core-free with a standard height of 24 cm (9 3/4 inches)

Ultra-thin filtering of suspended particles in water larger than 10 microns
clay, rust, tartar particles, sand

Changes about every 6 months