



-
- Setting the duration of the session: 0-60 minutes or continuous mode
 - Temperature setting: 35 to 60 degrees Celsius
 - Start-up and stop the steam generator
 - Control of the light from the control panel
 - Control panel size: 103-103-45 mm

The control panel can be installed in the damp room but we recommend that it be installed outdoors to keep it from temperature variations and humidity.

Pro series control unit

Thanks to the Desineo pro series control unit (provided), you will be able to network all the options of our range of Desineo pro series devices.

You'll be able to control everything from the control panel and from your smartphone

Options available (not provided) are:

Lighting kit (ref: tololedkit01boitier)

Perfume pump two perfume (ref: aromapump)

Automatic scaling pump (ref: descalingpump)

ON/OFF steam control button on demand (ref: onoffswitch)

Air extractor (ref: exhaustfan)

APP device allowing control of the generator through the steamtecsauna application (ref: appdevice)

Waterproof Pregnant Kit 2 X 80W With Deported Remote Control and Remote Control USB/Bluetooth/SD/FM Card (ref: tolo-music)

Water connection

1 In: Steam output (15/21)

2 In: Safety soup (15/21)



3 : Water inflamed - 20mm (15/21)

4 : Automatic emptying - 25 mm (20/27) to connect to your drain

Automatic functions

1. Auto-filling
2. Automatic heating
3. Automatic drainage