



6-seater STEAM room PRO 190 x 190 x 225 cm acrylic - door and windows ready to mount desineo



Product description:

6-seater STEAM room PRO full 190 x 190 x 225 cm in acrylic - door and windows ready to mount Desineo

Discover our full acrylic hammam cabin Desineo

Bring the comfort of the hammam home easily with this pre-installed kit

The front of the hammam cabin is fully glazed

The cabin has 6 moulded acrylic seats reinforced in fiberglass 8mm thick to ensure the solidity of the structure.

The vaulted roof will prevent condensation droplets from falling on users

This cabin is compatible with all our generators, accessories and lighting systems available on our website.

Technical features:

Seat height: 60 cm

Number of seats (moulded seats 8 mm thick): 6 seats



Thick door and windows: 5 mm

Sold in 7-part kit - waterproofing strips

Wall thickness: 63 mm

Dimensions: 190 x 190 x 225 cm

Vault-shaped ceiling

2-year warranty

6kw steam generator:

Suitable for a room of hammam 6 to 8 m³

Electrical power: 6 kw (single-phase or three-phase branching)

Automatic emptying, stainless steel vat.

Water consumption: 6 to 9 litres per hour in continuous operation

Dimensions: 425-160-315 mm

Weight: 12 kg

Control box and options

- Setting the duration of the session: 0-60 minutes or continuous mode
- Temperature setting: 35 to 60 degrees Celsius
- Start-up and stop the steam generator



-
- Control of the light from the control panel
 - Control panel size: 103-103-23 mm
 - time management of the session.

Electrical connection

Has : Electrical arrival that must be connected directly to your electric meter with the right fuse

B Exit of the cable that connects to the control box (5 meters) and the lighting precab

Also allows the passage of cables for lighting (not provided) controllable from the control box

Water connection

1 In: Steam output (15/21)

2 In: Safety soup (15/21)

3 : Water inflamed - 20mm (15/21)

4 : Automatic emptying - 25 mm (20/27) to connect to your drain

Automatic functions

1. Auto-filling:

The water infly electrovan will open automatically once the system is started and will fill

until the water level reaches the maximum level.

If the water level is still

below the minimum water level 10 minutes after defect of the water system



Work.

2. Automatic heating

The generator will compare the measured ambient temperature with the temperature

the number of resistances to be fed

3. Automatic drainage:

When time is up or the ON/OFF button is pressed down, the system drains automatically and displays "dd" on the LCD screen. The drain valve will be opened to drain. After a while, the system will open the intake valve for cool the tank and the resistance system will automatically shut down after drainage.

Special hammam air extraction fan

supplied fan (100-plus sheath compatible)

be careful to add a 12vdc transformer - switch in order to trigger it.

2 x 80W waterproof speakers kit with deputed remote control and USB/bluetooth/SD/FM card

Fancy music or ambient sound in any environment? Discover our waterproof 2x80 w speakers installable in your steam room, sauna, boat, kitchen, bathroom or any wetland!



Deported remote control and central control provided

Check your speakers where you want!

These speakers come with a central controller that lets you insert an SD card, an SB cable or simply connect your smartphone to Bluetooth.

The waterproof remote control gives you optimal remote control.

Technical features:

Waterproof index IP66 Cone size 6" Outer diameter 175.5mm Chassis size 145mm Depth 69mm Impedance 40h Frequency range 120HZ-20KHZ Max power 80w Grid Stainless aluminium Warranty 2 years old

9 3/4 filter door with its silicophosphate cartridge

Technical feature:

- Two-part filter equipped with a cartridge center to facilitate their replacement
- Events equipped with toric seals for perfect waterproofing.
- Brass inserts to avoid distorting tapping, a



source of subsequent leaks.

Maximum speed with cartridges: 1500L/h, Frost Fears, Entry/Exit 3/4 inch.

- Mounts before the devices to be protected
- Entry/Exit 20/27
- Maximum static pressure 5 bars
- The installation of a pressure reducer set to 4 bars is mandatory.
- It is recommended to install an anti-return valve at the exit of the filter door
- An anti-pollution valve upstream of the product and downstream of the water meter is required.
- Fears frost
- Climb to a dry place away from the light.
- Do not use sealing paste or seal paste, preferably use Teflon
- Leave a space of at least 5 cm under the tanks to facilitate maintenance
- 200 m³ treatment

Maintenance:

- Before changing the cartridge, cut off the water and unscrew the vents to put atmospheric pressure
- Loosen the tank with the key, then by hand



-
- Change the cartridge, and grease the toric seal of the tank with dietary grease
 - Replace the tank and tighten by hand, do not tighten the key. The key is only used to loosen the filter tanks
 - When re-watering, turn on the vents to flush out the air
 - The silicophosphate cartridge is to be replaced about every 6 months. Lifespan depends on the quality of your water and your use.
 - If not used for more than 2 days, run the water for 5 minutes before use
 - We recommend replacing the cartridge every 6 months to 1 year

Desineo peristaltic perfume pump

Discover the desineo perfume pump! A pump created especially for the aromatherapy of your hammam!

Easily spread your aromatherapy fragrances

Thanks to the Desineo perfume pump you can easily spread your aromatherapy fragrances

Its editing is very simple and its diffusion very effective since it works thanks to a peristaltic movement (a movement creating a depression)



Easy installation!

Its installation and its start-up sound very simple. The pump comes with a fitting with an anti-return valve to be placed directly on the T (after the steam output of your steam generator).

Another connection with anti-return valve is provided. Plunge it directly (with the hose) into your aromatherapy bottle and connect the hose to your pump.

(Don't forget to connect the circuit to a control button (or switch) to control its activation)

2-year warranty

220v air extraction fan to be connected with a 100 sheath. 12v power needed

Product gallery:



Product codes:

Reference: Cabineprohammamkey6b

EAN13: 3700830427981

UPC: -

